

# Safety Data Sheet

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### 1.1. Identification of the substance or preparation

Product Name : SS Ink Black

Product Code : SPC-0347K-2

### 1.2. Use of the substance/preparation

General Use : For ink jet

Product Description : Solvent pigment ink

### 1.3. Company/undertaking identification

#### MANUFACTURER

Company Name : Mimaki Engineering Co., Ltd

Address : 2182-3 Otsu, Shigeno, Tomi-shi, Nagano 389-0512 Japan

Telephone No. : +81-268-64-2413

Charge post : Inks and Media Division

Person in charge : Isao Tabayashi

E-mail address : tabayashi@mimaki.jp

#### IMPORTER/DISTRIBUTOR ESTABLISHED IN EU

Company Name : MIMAKI EUROPE B.V.

Address : Joan Muyskenweg 42-44, 1099CK Amsterdam

Telephone No. : +31-20-4627-640

Person in charge : Sakae Sagane

### 1.4. Emergency telephone

EMERGENCY : Mimaki Engineering Co., Ltd +81-268-64-2413

TELEPHONE : National Vaccine Information Center (NVIC)

NUMBER : +31-30-274888

## 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW : Black. Flammable liquid with a solvent odor. Irritating to eyes, skin and respiratory tract. Acute toxic substance. May cause organic solvent poisoning.



Xn, Xi This product is classified as 'Irritant' and 'Harmful'.

# Safety Data Sheet

## POTENTIAL HEALTH EFFECTS

- Inhalation : R20 Harmful by inhalation.  
 R37 Irritating to respiratory system.  
 R67 Vapours may cause drowsiness and dizziness.
- Eye : R36 Irritating to eyes.
- Skin : R21 Harmful in contact with skin.  
 R66 Repeated exposure may cause skin dryness or cracking.
- Ingestion : R22 Harmful if swallowed.
- Cancer-causing : R40 Limited evidence of a carcinogenic effect.

## POTENTIAL ENVIROMENTAL EFFECTS

- : Harmful to aquatic organisms.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

No	Chemical Name	Wt%	CAS No.	EINECS No.	Symbol letters	Risk Phrase	Chemical Formula
1	2-butoxyethyl acetate	70-80	112-07-2	203-933-3	Xn	20/21	C <sub>8</sub> H <sub>16</sub> O <sub>3</sub>
2	2-methoxy-1-methylethyl acetate	5-10	108-65-6	203-603-9	Xi	10-36	C <sub>6</sub> H <sub>12</sub> O <sub>3</sub>
3	N-butyl acetate	0.5-1.5	123-86-4	204-658-1	-	10-66-67	C <sub>6</sub> H <sub>12</sub> O <sub>2</sub>
4	3,5,5-trimethyl cyclohex-2-enone	10-20	78-59-1	201-126-0	Xn	21/22-36/37-40	C <sub>9</sub> H <sub>14</sub> O
5	Carbon black	2-8	1333-86-4	215-609-9	-	-	Unspecified

\*The wording of the symbol(s) and risk phrase(s) is specified in 16.OTHER INFORMATION.

### 4. FIRST AID MEASURES

- INHALATION : Fresh air, rest. Refer for medical attention.
- EYE : First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then take to a doctor.
- SKIN : Remove contaminated clothes. Rinse skin with plenty of water or shower. Rinse and then wash skin with water and soap. Refer for medical attention.

## Safety Data Sheet

INGESTION : Rinse mouth. Give plenty of water to drink. Give slurry of activated charcoal in water to drink. DO NOT induce vomiting. Refer for medical attention.

PROTECTION TO FIRST-AIDERS

: Please wear a tool for appropriate protection.

### 5. FIRE-FIGHTING MEASURES

FLAMMABLE : Flash point 71.0 deg C

PROPERTIES Flammable point 0.8-10.7%

Carbon monoxide occurs with harmful gas when this product burns.

EXTINGUISHING : Alcohol-resistant foam, carbon dioxide, powder.

MEDIA Do not use stick water.

FIRE FIGHTING : Remove inflammables immediately.

INSTRUCTIONS Perform the fire fighting from windward.

Wear full fire-fighting turn-out gear (full bunker gear) and respiratory protection (self-contained breathing apparatus).

### 6. ACCIDENTAL RELEASE MEASURES

Personal protection : Filter respirator for organic gases and vapours. Chemical protection suit. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Ventilation.

Method : Remove all ignition sources. Contain spilled liquid with sand or earth. DO NOT use combustible materials, such as sawdust. Absorb remaining liquid in sand or inert absorbent and remove to safe place. The material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

# Safety Data Sheet

## 7. HANDLING AND STORAGE

- HANDLING** : Handle in well-ventilated area. Avoid contact with skin, eyes, or clothing. Use proper protection (gloves, masks, aprons, goggles, etc.) Wash thoroughly after handling. To reduce potential for static discharge, bond and ground containers and equipment when transferring material.
- STORAGE** : Fireproof. Separated from strong oxidants, and strong bases. Cool. Keep in the dark. Dry.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Exposure limit values

No	Chemical Name	
1	2-butoxyethyl acetate	ACGIH 2007 TLVs and BEIs: TWA 20ppm MAK: 20 ppm, 130 mg/m <sup>3</sup> , H; Peak limitation category: II(4); Pregnancy risk group: C; (DFG 2003).
2	2-methoxy-1-methylethyl acetate	ACGIH 2007 TLVs and BEIs: TWA 150ppm, STEL 200ppm MAK: 50ppm, 275mg/m <sup>3</sup> (1996)
3	N-butyl acetate	ACGIH 2003 TLVs and BEIs: TWA 150ppm, STEL 200ppm MAK: 100ppm, 480mg/m <sup>3</sup>
4	3,5,5-trimethyl cyclohex-2-enone	ACGIH 2007 TLVs and BEIs: STEL Ceiling 5ppm MAK: 2ppm, 11mg/m <sup>3</sup>
5	Carbon black	ACGIH 2004 TLVs and BEIs: TWA: 3.5 mg/m <sup>3</sup>

### 8.2. Exposure controls

#### 8.2.1. Occupational exposure controls

**Engineering Controls** : Use exhaust ventilation to keep airborne concentration below exposure limits.

#### Personal Protection

**Respiratory Protection** : Wear gas masks for organic gases. Wear ventilation masks when working in closed area. An air purifying respirator with organic vapor cartridge or canister may be permissible under certain circumstances where air-borne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited.

## Safety Data Sheet

Eye Protection : Safety goggles, safety spectacles, face shield, or eye protection in combination with breathing protection. Wear coverall, chemical goggles and face shield when handling.

Skin Protection : Protective gloves. Protective clothing. Wear gloves that resist organic solvents and chemicals.

Ingestion : Do not eat, drink, or smoke during work.

### 8.2.2. Environmental exposure controls

: Not available

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. General information

Appearance - Physical state : Liquid

- Colour : Black

Odour : Solvent odor

### 9.2. Important health, safety and environmental information

pH : Not Applicable

Boiling Point / Boiling Range : 146 degree C or higher

Flash Point : 71.0 degree C

Flammable point : 0.8- 10.7%

Vapour Pressure : 1733Pa (20 degree C)

Relative density : 0.960±0.01 (20 degree C)

Solubility : Not available

Water solubility : Not available

Viscosity : Not available

### 9.3. Other information

Melting Point / Melting Range : Not available

Auto-Ignition Temperature :340 degree C

Specific Gravity : Not available

## 10. STABILITY AND REACTIVITY

CONDITONS TO AVOID : Fire. High temperature. High humidity. Sunlight.

STABILITY : Stable.

MATERIALS TO AVOID : Strong oxidants.

# Safety Data Sheet

HAZARDOUS : Carbon monoxide, low-molecular monomer gases  
 DECOMPOSITION PRODUCTS occurs with harmful gas when this product burns.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE TOXICITY

	Oral LD50	Dermal LD50	Inhalation LC50
2-butoxyethyl acetate	(mouse) 3200mg/kg (rat) 1600 mg/kg	(rabbit) 1480 mg/kg	(rat) 2400mg/kg
2-methoxy-1-methylethyl acetate	(rat) >2000 mg/kg	(rabbit) >2000 mg/kg	(rat) >20 mg/l / 6 hours
N-butyl acetate	(mouse) 7060 mg/kg (rat) 13100 mg/kg		(mouse) 6mg/m <sup>3</sup> /2h
3,5,5-trimethyl cyclohex-2-enone	(rat) 2330 mg/kg	(rabbit) 1500 mg/kg	

EYE IRRITATION : Irritating to eyes.

SKIN IRRITATION : Irritating to skin.

SENSITIZATION : Not available

MUTAGENICITY : Not available

### CARCINOGENICITY

	IARC	ACGIH	Others
2-butoxyethyl acetate		A3	
N-butyl acetate		A4	
3,5,5-trimethylcyclohex-2-enone		A3	EU67/548/EEC: 3, EPA 1986: C
Carbon black	2B	A4	

## 12. ECOLOGICAL INFORMATION

The substance is harmful to aquatic organisms. Handling is noted because it might influence the environment when leaking and abandoning it. Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

ECOTOXICITY : 2-butoxyethyl acetate  
 (Daphnia magna) EC50 67.5mg/l (48h)

## Safety Data Sheet

: 2-methoxy-1-methylethyl acetate

(Senastrum capricornutum) EC50 >1000mg/l (48h)

NOEC >1000mg/l (48h)

EC50 >1000mg/l (72h)

NOEC >1000mg/l (72h)

(Daphnia magna) EC50 370mg/l (48hr)

EC50 >100mg/l (21day)

NOEC >100mg/l (21day)

(Oryzias latipes) LC50 >100mg/l (96h)

LC50 64mg/l (14day)

NOEC 48mg/l (14day)

: N-butyl acetate

(Scenedesmus quadricauda) Toxicity Threshold 21000µg/l (7day)

(Daphnia magna) LC50 3200µg/l (2day)

NR 4400µg/l (2day)

(Lepomis macrochirus) LC50 100000µg/l (4day)

: 3,5,5-trimethylcyclohex-2-enone

(Senastrum capricornutum) EC50 170mg/l (48h)

NOEC 78mg/l (48h)

EC50 110mg/l (72h)

NOEC 43mg/l (72h)

(Daphnia magna) EC50 220mg/l (48hr)

EC50 >100mg/l (21day)

NOEC >100mg/l (21day)

(Oryzias latipes) LC50 >100mg/l (96h)

LC50 >100mg/l (14day)

NOEC 31mg/l (14day)

### PERSISTENCE AND DEGRADABILITY

: Not available

### BIOACCUMULATIVE POTENTIAL

: Octanol/water partition coefficient

(2-butoxyethyl acetate) log Pow: 1.51

(N-butyl acetate) log Pow: 1.82

(3,5,5-trimethylcyclohex-2-enone) log Pow: 1.67

RESULTS OF PBT ASSESSMENT: Not available

OTHER ADVERSE EFFECTS: Not available

## Safety Data Sheet

### 13. DISPOSAL CONSIDERATIONS

Have waste liquids, containers and other materials disposed of by licensed industrial waste contractors. Keep waste liquids from flushing containers, machines or other equipment from flowing directly to the ground or drainage. Dispose of wastes from drainage, combustion, etc, in compliance with laws and regulations on waste disposal or cleaning, or have them disposed of by contractors. To avoid harmful gases, do not use incinerators without flushing systems to burn wastes and other materials. Comply with all EU, national and local regulations. Do not dump this product into sewers, on the ground or into any body of water.

### 14. TRANSPORT INFORMATIONS

Check a thing without a leak in a container.  
 Perform prevention of collapse of cargo surely.  
 UN Number: Not applicable  
 Obey each laws and ordinances.

### 15. REGULATORY INFORMATION

This product is classified as follows and labeled accordingly.

Symbol



: Xn (Harmful)

Risk Phrase

: 20/21/22

(Harmful by inhalation, in contact with skin and if swallowed.)

36/37 (Irritating to eyes and respiratory system.)

40 (Limited evidence of a carcinogenic effect.)

66(Repeated exposure may cause skin dryness or cracking.)

67(Vapours may cause drowsiness and dizziness.)

Safety Advise

: 13 (Keep away from food, drink and animal foodstuffs.)

23 (Do not breathe vapour.)

24/25 (Avoid contact with skin and eyes.)

36/37/39

(Wear suitable protective clothing, gloves and eye/face protection.)

46 (If swallowed, seek medical advice immediately and show this container or label.)

Please refer to any other EU, national and local measures.

# Safety Data Sheet

## 16. OTHER INFORMATION

From clause 3

Symbol letters : Xn Harmful, Xi Irritant

Risk phrase : 10 Flammable.

20/21/22

Harmful by inhalation, in contact with skin and if swallowed.

36/37 Irritating to eyes and respiratory system.

40 Limited evidence of a carcinogenic effect.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.

### Revision history

Version	Date	Content
1.0	2008/02/01	First issue